

STEEL PIPE DIMENSIONS AND WEIGHTS SUMMARY

NPS	Outside Diameter		Wall Thickness		Sched	Weight Kg/Mtr	Weight Lb/ft	NPS	Outside Diameter		Wall Thickness		Sched	Weight Kg/Mtr	Weight Lb/ft
	in.	mm	in.	mm					in.	mm	in.	mm			
1/2"	0.840	21	0.109	2.769	40 STD	1.268	0.851	16"	16.000	406	0.188	4.775	10	47.290	31.748
			0.147	3.734	80 STD	1.621	1.088				0.219	5.563		54.980	36.910
3/4"	1.050	27	0.113	2.870	40 STD	1.684	1.131	18"	18.000	457	0.250	6.350	20	62.639	42.053
			0.154	3.912	80 STD	2.195	1.474				0.281	7.137		70.268	47.174
1"	1.315	33	0.133	3.378	40 STD	2.501	1.679	20"	20.000	508	0.312	7.925	30 STD	77.866	52.275
			0.179	4.547	80 STD	3.235	2.172				0.344	8.738		85.677	57.519
1 1/4"	1.660	42	0.140	3.556	40 STD	3.385	2.273	24"	24.000	610	0.375	9.525	40 XHY	93.213	62.578
			0.191	4.851	80 STD	4.464	2.997				0.438	11.125		108.433	72.797
1 1/2"	1.900	48	0.145	3.683	40 STD	4.048	2.718	30"	30.000	762	0.500	12.700	10	123.289	82.770
			0.200	5.080	80 STD	5.409	3.631				0.219	5.563		61.948	41.588
2"	2.375	60	0.154	3.912	40 STD	5.441	3.653	36"	36.000	914	0.250	6.350	20	78.547	52.733
			0.218	5.537	80 STD	7.480	5.022				0.281	7.137		88.458	59.386
2 1/2"	2.875	73	0.203	5.156	40 STD	8.629	5.793	42"	42.000	1067	0.312	7.925	30	97.208	65.176
			0.276	7.010	80 STD	11.411	7.661				0.375	9.525		105.144	70.588
3"	3.500	89	0.216	5.486	40 STD	11.284	7.576	48"	48.000	1219	0.438	11.125	40	122.369	82.152
			0.300	7.620	80 STD	15.272	10.253				0.500	12.700		139.198	93.450
4"	4.500	114	0.237	6.020		16.073	10.790	16"	16.000	406	0.562	14.275	40	155.904	104.666
			0.337	8.560		22.318	14.983				0.625	15.875		172.754	115.978
6"	6.625	168	0.188	4.775		19.252	12.924	18"	18.000	457	0.250	6.350	20 STD	78.547	52.733
			0.203	5.156		20.739	13.923				0.281	7.137		88.458	59.386
8"	8.625	219	0.219	5.563		22.318	14.983	20"	20.000	508	0.312	7.925	30 XHY	97.719	65.604
			0.250	6.350		25.354	17.021				0.375	9.525		117.075	78.598
10"	10.750	273	0.280	7.112	40 STD	28.263	18.974	24"	24.000	610	0.438	11.125	40	136.305	91.508
			0.312	7.925		31.334	21.036				0.500	12.700		155.106	104.130
12"	12.750	324	0.375	9.525		37.285	25.031	30"	30.000	762	0.594	15.088	30	183.378	123.110
			0.432	10.973	80 XHY	42.561	28.573				0.625	15.875		192.640	129.328
14"	14.000	356	0.500	12.700		48.719	32.708	36"	36.000	914	0.688	17.475	40	211.368	141.901
			0.188	4.775		25.233	16.940				0.750	19.050		277.401	186.233
16"	16.000	406	0.203	5.156		27.198	18.259	42"	42.000	1067	0.281	7.137	20 STD	106.029	71.183
			0.219	5.563		29.286	19.661				0.312	7.925		117.573	78.932
18"	18.000	457	0.250	6.350	20	33.308	22.361	48"	48.000	1219	0.375	9.525	30	140.938	94.618
			0.277	7.036	30	36.786	24.696				0.438	11.125		164.176	110.219
20"	20.000	508	0.322	8.179	40	42.532	28.554	16"	16.000	406	0.500	12.700	XHY	186.923	125.490
			0.375	9.525		49.216	33.041				0.625	15.875		232.410	156.028
24"	24.000	610	0.406	10.312	60	53.085	35.638	18"	18.000	457	0.688	17.475	40	255.148	171.293
			0.500	12.700	80 XHY	64.627	43.388				0.750	19.050		277.401	186.233
28"	28.000	711	0.594	15.088	80	95.969	64.429	20"	20.000	508	0.250	6.350	10	78.547	52.733
			0.188	4.775		31.588	21.207				0.281	7.137		88.458	59.386
30"	30.000	762	0.219	5.563		36.689	24.631	24"	24.000	610	0.312	7.925	20	106.029	71.183
			0.250	6.350	20	41.759	28.035				0.375	9.525		117.573	78.932
36"	36.000	914	0.307	7.798	30	51.002	34.240	30"	30.000	762	0.438	11.125	30 STD	176.731	118.648
			0.344	8.738		56.946	38.231				0.500	12.700		205.983	138.286
40"	40.000	1016	0.365	9.271	40 STD	60.301	40.483	36"	36.000	914	0.500	12.700	20 XHY	234.647	157.530
			0.438	11.125		71.852	48.238				0.625	15.875		292.066	196.078
42"	42.000	1067	0.500	12.700	60 XHY	81.53	54.735	42"	42.000	1067	0.688	17.475	30	320.817	215.380
			0.594	15.088	80	95.969	64.429				0.750	19.050		348.988	234.293
48"	48.000	1219	0.188	4.775		37.57	25.222	48"	48.000	1219	0.250	6.350	10	142.180	95.453
			0.219	5.563		43.657	29.309				0.281	7.137		159.672	107.196
54"	54.000	1375	0.250	6.350	20	49.713	33.375	16"	16.000	406	0.312	7.925	20	177.133	118.918
			0.281	7.137		55.739	37.420				0.375	9.525		212.525	142.678
60"	60.000	1524	0.312	7.925		61.735	41.445	18"	18.000	457	0.438	11.125	30	247.790	166.353
			0.375	9.525	STD	73.824	49.562				0.500	12.700		282.372	189.570
66"	66.000	1676	0.406	10.312	40	79.727	53.525	20"	20.000	508	0.625	15.875	40	351.723	236.128
			0.500	12.700	XHY	97.438	65.415				0.688	17.475		386.487	259.467
72"	72.000	1829	0.562	14.275	60	108.966	73.154	24"	24.000	610	0.750	19.050	40	420.576	282.353
			0.188	4.775		41.308	27.732				0.312	7.925		206.914	138.911
78"	78.000	1981	0.219	5.563		48.012	32.233	28"	28.000	711	0.375	9.525	STD	248.319	166.708
			0.250	6.350	10	54.685	36.713				0.500	12.700		330.097	221.610
84"	84.000	2133	0.281	7.137		61.327	41.172	30"	30.000	762	0.750	19.050	XHY	492.163	330.413
			0.312	7.925	20	67.939	45.611				0.375	9.525		284.112	190.738
90"	90.000	2286	0.375	9.525	30 STD	81.281	54.568	36"	36.000	914	0.438	11.125	40	331.404	222.487
			0.438	11.125	40	94.498	63.441				0.500	12.700		377.822	253.650
96"	96.000	2438	0.500	12.700	XHY	107.381	72.090	42"	42.000	1067	0.750	19.050	XHY	563.750	378.473
			0.625	15.875		132.983	89.278				0.875	22.225		655.969	440.383

All material contained in this publication is for general information only. This material should not, therefore, be used or relied upon for any specific application without independent competent professional examination and verification for its accuracy, suitability and applicability. Anyone making use of the material does so at his own risk and assumes any and all liability resulting from such use. Corpac Steel Products, Corp. disclaims any and all expressed or implied warranties of fitness for any general or particular purpose.

Ph: (305) 933-8599
 Fax: (305) 931-2251
 email: sales@corpacsteel.com

Corpac Steel Products, Corp
 20803 Biscayne Blvd., Ste 502
 Miami, FL 33180, USA